



SPL-1200 ULTRA

SMALL, POWERFUL, ELEGANT SUBWOOFERS WITH AUTO-EQ







Features

- Tiny cabinet dimensions
- An intuitive front panel interactive display
- One-button 7-band room bass correction
- DSP digital control
- Full feature remote control
- = 4 customized listening mode presets
- Patented Energy Recovery System (ERS) amplifiers (2400 watts Dynamic Power)

SPECIFICATIONS

Model	SPL-1200 Ultra
Woofer	12" forward firing (9.7" piston diameter)
"ERS" Class "D" Amplifier	2400 watts Dynamic 1200 watts RMS Power
High Pass Crossover	80 Hz (6 dB/octave)
Low Pass Crossover (Adjustable)	40 Hz-120 Hz 12 dB octave initial, 24 dB octave ultimate
Frequency Response Overall (+/-3 dB)	13-240 Hz 21-120 Hz
Harmonic Distortion	<5% (typical)
Magnet Structure	346 oz. (21.6 lbs.)
Voice Coil	3" Dual Layer inside/outside wound
Inputs	Line and Speaker Level
Outputs	Line-level, 80 Hz up
Phase	0°, 90°, 180°, 270°
Video Shielded	Yes
Dimensions (H/W/D) (inc. feet, grille and knobs)	15.5" x 14.9" x 18.3" (39.4 x 37.8 x 46.5 cm)
Cabinet	Sealed enclosure
Finish	Hand-rubbed black gloss lacquer or cherry veneer
Accessories	Mic, mic stand, and remote control
Warranty (parts/labor) (North America)	Three years (electronics) Five years (drivers)
Shipping Weight (approx.)	49 lbs. (22 Kg)